## **System Overview**



folder

access

· Slides out for easy

· UI has fold wizard

## **Specifications**

Side & end tamp

folding

Non-marking

ing for high quality

supports all color

print technologies

Input Channel

sets to 12mm

· Accumulates sub-

Field upgradeable

Inserter	<u>Min</u>	<u>Max</u>
Cycle speed		4,000 / Hr.
Envelope size	S65/DL	B4
Envelope (H x W)	105 x 225	353 x 353
Document (H x W)	93 x 210	300 x 315
Insert Thickness	60 gsm	12mm
Tower Feeder		
Feeders per Tower	3* (High Cap Bins)	6 (std. bins)
Towers per System	1	2
Stack Height	28mm (std. bin)	70mm (Hi cap bins)
Sheet Size (H x W)	93 x 210	300 x 315
Paper Weight	60 gsm	200 gsm
Booklet Feeder (opt)	80 gsm	8 mm
Accumulator / Folder		
Sheet Size	210 x 270	300 x 300
Fold Capacity (80 gsm)		7 pg "C", "Z" 10 pg Half

## **Optional Modules**

sets to 12mm

to 90 pages

station

Manual loading

Accumulates flats



- . Control reader / OMR, 1D & 2D
- . High capacity feed bin / 700 pg. capacity

to B4

• 12mm filling

Programmable

sealing levels

Automatically

thickness



- 70" Shingling output conveyor
- 1. Output reading / sequence verification



# Plockmatic Reflex

### Mid-range Inserting System

#### **Industry Leading Capabilities**

Simple and intuitive operation Automated job change-over Widest application range



### A unique solution for

- Short run jobs
- Automation of manual inserting
- Reprints processing
- Fast turn-around times

